



Cordless Impact Wrench

TW009GZ

40V MAX XGT • BL • XPT

Cordless 25.4mm (1") Square Drive D-Handle Impact Wrench with Short Anvil.

Delivers a powerful combination of high torque and excellent manoeuvrability, designed to replace air impact wrenches for tightening large-diameter bolts. Supplied without battery and charger, and packaged in a durable plastic carry case.



TECHNICAL

SPECIFICATIONS

Square Drive	1" (25.4 mm)
Anvil Length	163 mm
Max Fastening Torque	3,150 N·m
Nut-busting Torque	4,000 N·m
Fastening Torque	Max/ Hard / Med. / Soft: 2,850 / 1,600 / 1,000 / 600 N·m
Fastening Capacities	Standard Bolt: M27 - M45 / High Strength Bolt: M20 - M33
No Load Speed	Max/Hard/Med./Soft: 0-1,200/0-850/0-700/0-600 min-1
Impacts per minute (IPM)	Max/Hard/Med./Soft: 0-1,750/0-1,500/0-1,300/0-1,200
Dimensions(LxWxH)	435 x 135 x 297 mm (with BL4050F)
Net Weight	10.0 kg (without battery)

USER BENEFITS

- **Pneumatic Replacement:** Delivers up to 3,150 Nm of fastening torque, providing the power of an air impact wrench without the need for hoses or compressors.
- **Full Speed Mode:** Reaches maximum velocity with significantly less trigger pull, reducing hand fatigue during repetitive, high-volume fastening tasks.
- **Versatile Power Settings:** Features a 4-stage electronic impact selection (Max, Hard, Medium, Soft) to prevent over-tightening or damaging smaller bolts.
- **Auto-Stop System:** Offers three reaction modes for both forward and reverse rotations, preventing nuts from flying off or bolts from being over-stressed.
- **Shadow-Free Workspace:** The ring illumination LED surrounds the drive, eliminating the "socket shadow" typically found with single-bulb designs for better visibility in tight, dark spaces.
- **Low Reaction Force:** A vertical motor design minimizes the torque reaction felt by the user at startup, improving safety and tool control.
- **Toolless Side Handle:** Can be adjusted 360° without additional tools, allowing users to quickly adapt to different working angles and positions.
- **Battery Vibration Protection:** An independent, rubberized battery housing isolates the power source from the tool's impact vibrations, protecting terminals and extending battery life.
- **Jobsite Resilience:** Built with XPT (eXtreme Protection Technology) to guard against dust and water in harsh outdoor or industrial environments.
- **Glove-Friendly Trigger:** The large two-finger trigger is shaped specifically for easy operation while wearing heavy industrial gloves.
- **Tool Hanger Ring:** Includes a large steel ring for easy storage or hanging on framework during steel erection work.

Link to Product page - <https://makitauae.com/product/tw009gz/>