



Impact Wrench

TW0350

400 W • 1/2" • 350 Nm

High-torque impact wrench

An efficient 1/2" drive impact wrench with a 400 W motor and max. torque of 350 Nm. An easy-to-use tool for high-torque applications. Reverse function.



TECHNICAL

SPECIFICATIONS

MAXIMUM OUTPUT POWER	400 W
IMPACT	2000 min? ¹
SOUND POWER LEVEL (LWA)	104 dB(A)
SOUND PRESSURE LEVEL (LPA)	93 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
VIBRATION LEVEL (3 AXES)	11,5 m/s ²
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
WEIGHT WITHOUT CABLE (EPTA-PROCEDURE 01/2003)	3,0 kg
PRODUCT DIMENSIONS (L X W X H):	283 x 87 x 233 mm
EAN	88381051309
NO LOAD SPEED	2000 min? ¹
MAX FASTENING TORQUE IMPACT DRILL	350 Nm
TIGHTENING CAPACITY STANDARD BOLT	M12 - M22
VIBRATION LEVEL (3 AXES), FASTENING BOLT	11,5 m/s ²
DRIVE SQUARE	1/2 "

USER BENEFITS

- The rubber coating on the handle ensures a firm working grip

Link to Product page - <https://makitauae.com/product/tw0350-impact-wrench/>