

## **Blower XGT®**

## UB001GZ

40V MAX • 64 m/s • 16.0 m<sup>3</sup>/min

UB001G delivers the high output to tackle more demanding applications with

A combination of a brushless motor and XGT system produces 64m/s of max air velocity, 16.0m<sup>3</sup>/min max air volume, and 17Nm blowing force, the user has enough power to tackle any job.



## **SPECIFICATIONS**

Nominal Battery Voltage Voltage XGT

Battery protection

No load speed

Max. Air Velocity

Air volume

Sound Power Level (LWA)

Sound Pressure Level (LpA) Noise Uncertainty (K Factor)

Vibration Level (3 axes)

Vibration Uncertainty (K Factor)

Tool weight with battery (EPTA)

Product Dimensions (L x W x H):

Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)

40 V

Yes

Yes

0 - 20 000 / 23 000 min?1

53 / 64 m/s

0 -13,5 / 16 m<sup>3</sup>/min

94,1 dB(A)

83,7 dB(A)

3,1 dB(A)

? 2,5 m/s<sup>2</sup>

1.5 m/s<sup>2</sup>

3,1 - 4,5 kg

905 - 1017 x 167 x 297 mm

Li-ion

## **USER BENEFITS**

- Max blowing force can be easily obtained by fully pulling the trigger (Boost mode)
- Compact and lightweight for single-handed operation
- Lock-on button operable from either side of the handle for continuous operation
- High power and less user fatigue
- The best choices for use in resorts, public places, and residential areas

Link to Product page - https://makitauae.com/product/ub001gz-blower-xgt/