



Backback Blower

UB004CZ

36V • 28 N • 20.9 m²/min • 23,800 min?¹

Powered by Portable Power Pack Units.

The high blowing efficiency (28N) of this device is comparable to that of a 65cm³ engine backpack blower. The airflow path has been optimized from a curved line to a straight.



TECHNICAL

SPECIFICATIONS

Blowing force	5, 15, 25 N
Max. Air Velocity	33.2 / 59.0 / 76.3 m/s
Air volume	8.5 / 15.2 / 19.7 m ³ /min
No load speed	0 - 22000 min? ¹
Continuous Use PDC1200	500 - 55 min
Sound Pressure Level	82,3 dB(A)
Sound Power Level (LWA)	96,1 dB(A)
Battery Voltage	36 V
Tool weight with battery (EPTA)	18.6 - 16.5 kg

USER BENEFITS

- 3 speed mode, Boost mode, Variable Speed Control by Trigger + Cruise Control Lever
- \hat{A} The machine operates at a high blowing force of 25N with no time limit, and at 28N in Boost mode with a time limit
- \hat{A} The airflow path from the fan to nozzle is designed to be straight, providing a high blowing force
- \hat{A} Improved backpack harness section for more comfortable backpacking experience
- \hat{A} The grip position is adjustable forward / backward and left / right to suit user's size or work posture
- \hat{A} Continuous run time @5N : 500 min / @25N : 55 min
- \hat{A} eXtreme Protection Technology / IPX4 compatible : High water-resistance allows to operate the machine even if it is wet with water
- \hat{A} Use with optional Portable Power Pack Units PDC1500 or PDC1200

Link to Product page - <https://makitauae.com/product/ub004cz/>