



Cordless Concrete Vibrator XGT®

VR001G

40Vmax • 12 000 – 15 000 min?¹

XGT® Battery powered Concrete Vibrator for professionals

Concrete vibrator powered by 40Vmax XGT battery with two 2 operating modes. VR001G series supports a larger vibration part diameter than the current model and transmits vibration to a wider range to improve compaction efficiency thanks to 40Vmax XGT® Li-Ion battery and BL motor. (Note:- Flexible shafts are sold separately and it is not available with the machine VR001G as standard)



TECHNICAL

SPECIFICATIONS

Voltage XGT	Yes
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Battery protection	Yes
Vibrations per minute	12 000 - 15 500 min? ¹
Vibrator Shaft Diameter	28 - 38 mm
Sound Pressure Level (LpA)	80 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	4.9 m/s ²
Vibration Uncertainty (K Factor)	1.5 m/s ²
Product net weight	1.4 kg
Tool weight with battery (EPTA)	4.8 - 7.8 kg
Product Dimensions (L x W x H):	282 x 112 x 258 mm

USER BENEFITS

Link to Product page - <https://makitauae.com/product/vr001g-cordless-concrete-vibrator-xgt/>