



Concrete Vibrator XGT ® / LXT ®

VR002C

36V • 43 mm x 3 m • 12 000 min?¹

Powerful Concrete Vibrator which is powered by portable Backpack Batteries.

This Concrete Vibrator is powered by Powered by PDC01/PDC1200 portable power pack. Less user fatigue due to the battery weight transferred from the tool body to the portable power pack on user's back.



TECHNICAL

SPECIFICATIONS

Voltage XGT/LXT	Yes
Nominal Battery Voltage	40 V/36V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibrations per minute	12 000 min? ¹
Vibrator Shaft Diameter	43 mm
Vibrator Shaft Length	3000 mm
Vibration Level (3 axes)	? 2.5 m/s ²
Product net weight	7.2 kg
Tool weight with battery (EPTA)	12.9 kg

USER BENEFITS

- High frequency motor is placed in the vibration section to rotate the vibration weight directly without rotation transmitting rod
- Inside the shaft pipe, there run only lead wires and no rotation transmitting rod, making the flexible shaft lightweight
- Powered by PDC1200/ PDC01 portable power pack (optional)
- Less user fatigue due to the battery weight transferred from the tool body to the portable power pack on user's back
- Lower vibration transmitted to user
- Run time VR004C: 200min with PDC1200 / 60min with PDC01
- Run time VR002C: 300min / with PDC1200 / 100min with PDC01

Link to Product page - <https://makitauae.com/product/vr002c-concrete-vibrator-xgt-lxt/>